



型号 (1 代码 · 2 模数) — (3 齿数) — (4 厚度B) — (5 齿轮形状) — (6 轴径)
CFABK2.5 — 30 — 25 — B — 16N

■ 请按步骤 ①~⑥ 选择型号和参数后进行订购。



型号区分: **代码** **7** 天发货

■ B形状

代码			材质	表面处理	附件
圆孔	圆孔+螺纹孔	键槽孔+螺纹孔			
CFAHB	CFAB	CFAKB	S45C	-	固定螺丝
CFAHBB	CFABB	CFAKBB		发黑	

轴孔规格

圆孔	圆孔+螺纹孔

⑤ B形

① 未指定齿轮形状时, 齿轮形状为B。

型号		④ 齿数	④ 厚度B	⑤ 齿轮形状	⑥ 轴孔直径P _{H7} 最小单位1mm		d 基准圆直径	D 齿顶圆直径	G 齿根圆直径	H	L	l ₁	l ₂	M (粗牙螺纹)
① 代码	② 模数				圆孔	键槽孔+螺纹孔								
圆孔 CFAHB CFAHBB	2.5	12	25	B	8~13	8N	30	35	23.75	23	37	12	6	M5
		14			8~15	8N · 10N~12N	35	40	28.75	25				
		15			8~20	8N · 10N~15N	37.5	42.5	31.25	30				
		16			8~22	8N · 10N~17N	40	45	33.75	32				
		18			8~26	8N · 10N~22N	45	50	38.75	38				
		19			8~27	8N · 10N~22N	47.5	52.5	41.25	39				
		20			8~28	8N · 10N~23N	50	55	43.75	40				
		22			8~32	8N · 10N~29N	55	60	48.75	44				
		24			8~36	8N · 10N~32N	60	65	53.75	48				
		25			8~38	8N · 10N~33N	62.5	67.5	56.25	50				
		26			8~43	8N · 10N~37N	65	70	58.75	50				
		28			8~48	8N · 10N~40N	70	75	63.75	55				
		30			8~51	8N · 10N~43N	75	80	68.75	65				
		32			8~55	8N · 10N~47N	80	85	73.75	70				
		34					85	90	78.75	70				
		35			10~55	10N~47N	87.5	92.5	81.25	75				
		36			10~57	10N~49N	90	95	83.75	75				
		40					100	105	93.75	80				
		42					105	110	98.75	80				
		45					112.5	117.5	106.25	85				
48			120	125	113.75	85								
50			125	130	118.75	85								
52			130	135	123.75	85								
60			150	155	143.75	85								



型号 (1 代码 · 2 模数) — (3 齿数) — (4 厚度B) — (5 齿轮形状) — (6 轴径) — (etc)
CFABK2.5 — 20 — 25 — B — 10N — KC90

可选加工	止动螺丝孔追加加工 KC90 · KC120	追加螺丝孔加工 TPC										
技术说明		<table border="1"> <thead> <tr> <th>变更前螺纹孔</th> <th>TPC(变更后)</th> </tr> </thead> <tbody> <tr> <td>M3</td> <td>M4</td> </tr> <tr> <td>M4</td> <td>M3 M5</td> </tr> <tr> <td>M5</td> <td>M4 M6</td> </tr> <tr> <td>M6</td> <td>M5 M8</td> </tr> </tbody> </table>	变更前螺纹孔	TPC(变更后)	M3	M4	M4	M3 M5	M5	M4 M6	M6	M5 M8
变更前螺纹孔	TPC(变更后)											
M3	M4											
M4	M3 M5											
M5	M4 M6											
M6	M5 M8											
可选加工	台阶孔 DHL · DHR	两端台阶孔 WDH										
技术说明												
可选加工	轮毂切割 BS											
技术说明	<p>指定方法 BS.5</p> <p>以0.5mm为单位切割轮毂长度。</p> <ul style="list-style-type: none"> ① 圆孔型: 0 ≤ BS ≤ ℓ ① 圆孔+螺纹孔型: M+3 ≤ BS ≤ ℓ ① 键槽孔+螺纹孔型: M+3 ≤ BS ≤ ℓ 											