



型号(①代码·②M) — ③L
EBSC2 — 3

■请按步骤①~③选择型号和参数后进行订购。



型号区分: ④代码 **5** 天发货

代码	材质	强度分类
EBSC	SUS304	A2-70

① JIS B 1176

M×P(粗牙螺纹)	A	E	B
2×0.4	3.8	2	1.5
2.5×0.45	4.5	2.5	2
2.6×0.45	4.5	2.6	2
3×0.5	5.5	3	2.5
4×0.7	7	4	3
5×0.8	8.5	5	4
6×1.0	10	6	5
8×1.25	13	8	6
10×1.5	16	10	8

※强度分类是指螺栓的抗拉强度。
(例)A2-70
表示抗拉强度的最小值为700N/mm²。
钢分类为A2(奥氏体不锈钢)

【不锈钢型】

型号		ℓ	型号		ℓ
① 代码	②M-③L		① 代码	②M-③L	
EBSC (不锈钢)	2- 3	全 螺 纹	EBSC (不锈钢)	3- 4	全 螺 纹
	4			5	
	5			6	
	6			8	
	8			10	
	10			12	
	12			14	
	15			15	
	15			16	
	15			18	
	2.5- 4	全 螺 纹		20	18
	5			25	
	6			30	
	8			35	
	10			40	
	12				
	15				
	2.6- 4	全 螺 纹		4- 5	全 螺 纹
	5			6	
	6			8	
	8			10	
	10			12	
	12			14	
	15			15	
15	16				
15	18				
15	20				
15	22				
15	25				