



型号(1代码·2D) — (3)L
EASTM6 — 20

■请按步骤①~③选择型号和参数后进行订购。




型号区分: 7天发货
代码

■一端螺纹型(公差p6·m6)




代码	D公差	材质	硬度
EAST	p6	SUJ2	45~50HRC
EASTM	m6		


EAST



EASTM




通气槽深度



l ₁	l ₂	M×P	l	Dp6	型号		③L
					①代码	②D	
1.5	0.5	3×0.5	*6	+0.020 +0.012	EAST (P6型)	5	10 15 20 25 30
		4×0.7	*8	+0.024 +0.015		6	10 15 20 25 30 35 40 50
2.0	0.5	5×0.8	10			+0.029 +0.018	8
		6×1.0		10			15 20 25 30 35 40 45 50 60 70 80
2.5	1.0	8×1.25	15	+0.029 +0.018		12	20 30 40 50 60 70 80
						13	40 50 60 70 80
3.0	1.0	10×1.5	18	+0.035 +0.022		16	40 50 60 70 80
						20	50 60 70 80

l ₁	l ₂	M×P	l	Dm6	型号		③L
					①代码	②D	
1.5	0.3	3×0.5	*6	+0.012 +0.004	EASTM (M6型)	5	10 15 20 25 30
		4×0.7	*8	+0.015 +0.006		6	10 15 20 25 30 35 40 50
2.0	0.5	5×0.8	10			+0.018 +0.007	8
		6×1.0		10			15 20 25 30 35 40 45 50 60 70 80
2.5	1.0	8×1.25	15	+0.018 +0.007		12	20 30 40 50 60 70 80
						13	40 50 60 70 80
3.0	1.5	10×1.5	18	+0.021 +0.008		16	40 50 60 70 80
						20	50 60 70 80

■锥形螺纹型



代码		材质	硬度	
EAMT		SK4	45~50HRC	

M×P	l	型号		③L	
		①代码	②D		
5×0.8	9	EAMT	8	30	40
6×1.0	10		10	40	50
8×1.25	14		12	40	50
10×1.5	16		13	50	60
			16	60	70