



# 固定环

## 紧凑型/平衡型 分离型



代码	材质	表面处理	附件
ACSPJ	S45C	发黑	2个内六角螺栓
ACPSPJ		无电解镀铬	2个内六角螺栓
ACSSPJ	SUS304	—	(SUS)

1 代码 2 D — 3 B  
 选型示范 ACSPJ 20 — 8

■ 请按步骤①~③选择型号和参数后进行订购。

交货期 型号区分: 7 天发货  
代码

型号	② D	③ B	D1	M (粗牙螺纹)	d	H	C	X	Y	(W)
(紧凑型) ACSPJ ACPSPJ ACSSPJ	6	6	18	M2.6	2.9	4.9	0.5	6	3	1
	8		7					1.5		
	10		8							
	12		9							
	15	8	30	M3	3.4	6	0.5	11	3	1.5
	16		11.5							
	20		13					5		
	25		16.5					5		
	30	10	50	M4	4.5	7.5	0.5	20	5	1.5
	35		22.5					6		
	40		25							
	50		32					15		
		18	M8	9	14	1	32	15	3	



代码	材质	表面处理	附件
ACSPB	S45C	发黑	2个内六角螺栓
ACPSPB		无电解镀铬	2个内六角螺栓
ACSSPB	SUS304	—	(SUS)

型号	② D	③ B	D1	M (粗牙螺纹)	d	H	C	X	Y	(W)					
(平衡型) ACSPB ACPSPB ACSSPB	16	10	35	M 5	5.5	9	0.5	12	6	1.5					
	17										10	7			
	20	12	40					15	8						
		12						17	7						
	25	15	45					M 6	6.6		12	1	20	10	2
		12						M 5	5.5		9				
	30	15	50	M 6	6.6	12	18	23	12	13					
		20									M 8	9	14		
	35	15	60	M 6	6.6	12	26	16	3						
	40	18	70	M 8	9	14	32	16	3						
	50	22	85	M10	11	18									

紧凑性比较表						
D	紧凑程度的差值		紧凑型		标准型	
	B (壁厚)	D1 (外径)	B (壁厚)	D1 (外径)	B (壁厚)	D1 (外径)
6	-2	-2	6	18	8	20
8	-2	-3	6	22	8	25
10	-2	-5	6	25	8	30
12	-2	-5	6	25	8	30
15	-2	-4	8	30	10	34
16	-2	-5	8	30	10	35
20	-2	-5	8	35	10	40
25	-2	-3	10	42	12	45
30	-3	-5	12	50	15	55
35	-3	-5	12	55	15	60
40	-6	-10	12	60	18	70
50	-4	-5	18	80	22	85

■ 重量差的比较表

① 代码	型号	② D	③ B	单个主体重量 (g)			带螺栓重量 (g)		
				上侧	下侧	重量差	上侧	下侧	重量差
ACSP (常用产品)	25	40	12	45	40	5	48	45	3
			18	141	163	22	162	173	11
ACSPB (平衡型)	25	40	12	43	43	0	47	47	0
			18	152	152	0	167	167	0