



开口型

① D: 为线切割加工前的公差。

开口

代码	材质	表面处理	附件
ACD	S45C	发黑	1个内六角螺栓(SCM435)
ACPD		无电解镀锌	1个内六角螺栓(不锈钢)
ACSD	SUS304	—	

分离型

分离

代码	材质	表面处理	附件
ACSPD	S45C	发黑	2个内六角螺栓(SCM435)
ACPSPD		无电解镀锌	2个内六角螺栓(不锈钢)
ACSSPD	SUS304	—	

① 代码 ② D

ACD 15

■ 请按步骤 ①~② 选择型号和参数后进行订购。

型号区分: **7** 天发货

型号		B	D ₁	B ₁	t	M (粗牙螺纹)	d	H	C	X	(Z)	Y	(W)		
① 代码	② D														
(开口型) ACD ACPD ACSD	3	10	15	8	2	M3	3.4	6	0.5	4.5	5	3	1		
	4										6				
	5	12	20	10	3	M4	4.5	7.5		6	7	4			
	6									6.5					
	8									9	10	5			
	10									10	12.5	6			
(分离型) ACSPD ACPSPD ACSSPD	12	18	30	15	5	M6	7	12	1.0	11	12.5	6	1.5		
	15									13	13	8			
	16	20	45	18	5	M8	9	14		13	13	8			
	20									15	15	10			
	25									18	18	10			
	30									20	20	10			
	35	23	70	18	5	M8	9	14		23	21	12		2	
	40									26	23	13			
	50	27	85	22			M10	11		18	32	28		16	

① ACD的D尺寸公差为+0.01~+0.08。