



1 代码 2 D — 3 公称型号
FFJBNC6 — 2


■ 请按步骤 1~3 选择型号和参数后进行订购。



型号区分：
代码 5 天发货

■ 三通压合接头

FFCTPT




材质 SUS316

型号		螺纹尺寸 R (PT)	适用气管 外径 (mm)	适用管 内径 (mm)	L ₁	L ₂	A	B	对边间距								
1 代码	2 No.								H ₁	H ₂							
FFCTPT	4-1	1/8	4	2.5	20	18	9	6	12	10							
	4-2	1/4									21	21	11	6	14	10	
	6-1	1/8	6	4	21.5	18	9	7	12	12							
	6-2	1/4									22.5	21	11	7	14	12	
	8-1	1/8	8	5	23.5	19	9	7.5	14	14							
	8-1	1/8									6	23.5	19	9	7.5	14	14
	8-2	1/4									6	23.5	21	11	7.5	14	14
	8-3	3/8									6	25	23	12	7.5	17	14
	8-3	3/8	8	6	25	23	12	7.5	17	14							
	10-2	1/4									8	28.5	25	11	8	22	17
	10-3	3/8	10	6.5	28.5	26	12	8	8	22	17						
	10-3	3/8										8	28.5	26	12	8	22
	12-2	1/4	12	8	30	26	11	9.5	22	19							
	12-2	1/4									10	30	26	11	9.5	22	19
12-3	3/8	10									30	27	12	9.5	22	19	

■ 三通压合接头

FFCUT




材质 SUS316

型号		适用气管 外径 (mm)	适用管 内径 (mm)	L	B	对边间距	
1 代码	2 No.					H ₁	H ₂
FFCUT	4	4	2.5	20	6	12	10
	6	6	4	21.5	7	12	12
	8-5	8	5	23.5	7.5	14	14
	8	8	6	23.5	7.5	14	14
	10	10	8	28.5	8	22	17
	12-8	12	8	30	9.5	22	19
	12-9	12	9	30	9.5	22	19
12	12	10	30	9.5	22	19	

■ 直立压合接头

FFJBNC



材质 黄铜

型号		适用气管 外径 (mm)	公称型号	气管内径 (mm)	L	L ₁	B	H ₁	H ₂	T R (PT)	重量 (g)
1 代码	2 No.										
FFJBNC	6	1	4	4	26	22	12.5	12	12	R1/8	18
					28.5	22.5		14	12	R1/4	26
	8	1	5	5	28	24	14	14	14	R1/8	25
					30	24		14	14	R1/4	30
	10	2	6.5	6.5	31	24.6	15.5	17	14	R3/8	41
					32	26		17	17	R1/4	43
	12	3	8	8	33	26.6	17	17	17	R3/8	50
					34	28		17	19	R1/4	49
					35	28.6		17	19	R3/8	57