




型号(1)代码·(2)D — (3)L
 EASCM4 — 12
 EASV2 — 6

■请按步骤1~3选择型号和参数后进行订购。



型号区分: 7天发货
 代码



C	型号		(3)L								
	(1) 代码	(2) D									
0.3 以下	EASCM	2	6	8	10	12	15				
		3				10	12	15	20		
		4				10	12	15	20		
0.5		5				10	12	15	20		
		6				10	12	15	20	25	

代码	材质	硬度
EASCM	SUS440C	58HRC~
EASCSM	SUS304	-

C	型号		(3)L								
	(1) 代码	(2) D									
0.3 以下	EASCSM	2	6	8	10	12	15				
		3				10	12	15	20		
		4				10	12	15	20		
0.5		5				10	12	15	20		
		6				10	12	15	20	25	



l1	l2	型号		(3)L							
		(1) 代码	(2) D								
1	0.2	EASV	2	6	8	10					
			3	8	10	15	20	25	30		
			4	10	15	20	25	30			
1.5	0.5		5	10	15	20	25	30			
			6	10	15	20	25	30			
2	0.5		8				20	30	40		
2.5						20	30	40			
3						30	40	50	60		

代码	材质	硬度
EASV	SUJ2	58HRC~
EASVC	SUS440C	58HRC~

l1	l2	型号		(3)L									
		(1) 代码	(2) D										
0.4	0.1		1	5	6	8	10						
0.6			1.5	5	6	8	10						
1	0.2	EASVC	2	5	6	8	10						
			3	6	8	10	15	20	25	30			
			4	8	10	15	20	25	30				
1.5	0.5		5				10	15	20	25	30		
			6				10	15	20	25	30		
2	0.5		8				20	30	40				
2.5						20	30	40					
3						30	40	50	60				