



①代码 ②D — ③公称型号
 FFLELLSS 4
 FFLBULSS 10

■请按步骤①~③选择型号和参数后进行订购。




型号区分：
 代码 **5** 天发货

外螺纹直立接头



FFLCNLSS




材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	③公称型号	A	对边距离 H	L	螺纹尺寸 M	重量 (g)
FFLCNLSS	4	M5	1	21.5	10	18.5	M5×0.8	26.8
			2	21	10	17	R1/8	27.6
			3	19.5	14	14	R1/4	33.9
	6	M5	1	23.5	12	21.5	M5×0.8	26.7
			2	23	12	19	R1/8	27.5
			3	23.5	14	17	R1/4	35.0
8	1	2	1	27.5	14	23.5	R3/8	45.0
			2	26.5	14	21	R1/4	38.0
			3	22	17	16	R3/8	41.7
	2	3	1	32.5	17	24	R1/4	60.1
			2	28.5	17	22.5	R3/8	68.6
			3	26.5	22	19	R1/2	91.4
12	3	4	1	30.5	19	24.5	R3/8	116.2
			2	29.5	22	22.5	R1/2	131.8

外螺纹弯接头



FFLELLSS




材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	③公称型号	A	B	P	对边距离 H	L	螺纹尺寸 M	重量 (g)	
FFLELLSS	4	M5	1	18	22.5	12	12	20.5	M5×0.8	6.5	
				2	24.5		12	20.5	R1/8	8.9	
				3	27.5		14	22	R1/4	14.8	
			2	M5	1		23.5	12	21.5	M5×0.8	9.8
					2		25.5	12	21.5	R1/8	10.9
					3		28.5	14	23	R1/4	16.0
	6	1	2	23.5	29.5	17	23.5	R3/8	23.9		
				2	26.5	14	22.5	R1/8	17.6		
				3	29.5	17	25.5	R3/8	23.1		
		2	3	1	31.5	17	26	R1/4	23.6		
				2	33	17	27	R3/8	28.4		
				3	36	22	28.5	R1/2	44.8		
10	3	4	1	34.5	22	28.5	R3/8	30.3			
			2	37.5	22	30	R1/2	46.4			

直管接头



FFNSTLS




材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	L	P	重量 (g)
FFNSTLS	4	M5	34	10	11.5
			37	12	15.8
			40	14	21.3
			45	17	34.3
			48	20	47.0

三通接头



FFNTELS




材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	A	P	重量 (g)
FFNTELS	4	M5	19	12	29.8
			21.5	12	29.7
			24	14	42.3
			27.5	17	66.4
			30	22	124.6

弯接头



FFNEBLS




材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	A	P	重量 (g)
FFNEBLS	4	M5	19	12	23.2
			21.5	12	23.1
			24	14	32.5
			27.5	17	57.1
			30	22	107.0

阀接头



FFLBULSS



材质 SUS316(密封: 氟橡胶)

型号	①代码	②D	L	对边距离 H	螺纹尺寸 M	C (max)	重量 (g)
FFLBULSS	4	M5	33.5	14	M12×1.0	4	18.8
			36.5	17	M14×1.0	6	29.3
			40.5	19	M16×1.0	9	38.0
			45.5	23	M20×1.0	11.5	63.5
			48.5	26	M22×1.0	11.5	79.3

规格

使用流体	空气、水
最高使用压力	1.0MPa
使用真空压力	-100kPa
使用温度范围*	-15~120℃

橡皮管·快速接头
吸盘及配件

41