



1 代码 2 外径 — 3 长度 — 4 气管颜色  
FEPU 6 — 100 — B

■ 请按步骤 ①~④ 选择型号和参数后进行订购。



型号区分: 代码 **5** 天发货



■ 聚氨酯气管

| 型号   |           | ③ 尺寸固定型长度 (m) | ④ 气管颜色   | 内径 (mm) | 最小曲率半径 (mm) | 外径精度 (mm)     | 重量 (kg/m) |
|------|-----------|---------------|--|---------|-------------|---------------|-----------|
| ① 代码 | ② 外径 (mm) |               |  |         |             |               |           |
| FEPU | 4         | 10            | B (黑色)<br>G (绿色)<br>BL (蓝色)<br>R (红色)<br>Y (黄色)<br>W (白色)<br>C (透明)<br>CB (透明蓝色) | 2.5     | 5           | ±0.1          | 0.009     |
|      |           | 20            |  |         |             |               |           |
|      |           | 100           |  |         |             |               |           |
|      | 6         | 10            |  | 4       | 12          |               |           |
|      |           | 20            |  |         |             |               |           |
|      |           | 100           |  |         |             |               |           |
|      | 8         | 10            |  | 5       | 15          |               |           |
|      |           | 20            |  |         |             |               |           |
|      |           | 100           |  |         |             |               |           |
|      | 10        | 10            |  | 6.5     | 25          | +0.1<br>-0.15 | 0.055     |
|      |           | 20            |  |         |             |               |           |
|      |           | 100           |  |         |             |               |           |
| 12   | 10        | 8             | 28   |         |             |               |           |
|      | 20        |               |  |         |             |               |           |
|      | 100       |               |  |         |             |               |           |
| 16   | 10        | 11            | 30   | 0.127   |             |               |           |
|      | 20        |               |  |         |             |               |           |



■ 尼龙气管

| 型号    |           | ③ 尺寸固定型长度 (m) | ④ 气管颜色           | 内径 (mm) | 最小曲率半径 (mm) | 外径精度 (mm) | 破坏压力 (MPa) | 常用压力 (MPa) | 重量 (kg/m) |
|-------|-----------|---------------|------------------|---------|-------------|-----------|------------|------------|-----------|
| ① 代码  | ② 外径 (mm) |               |                  |         |             |           |            |            |           |
| FEPUN | 4         | 10            | B (黑色)<br>W (白色) | 2.5     | 10          | ±0.05     | 6.0        | 2.0        | 0.008     |
|       |           | 20            |                  |         |             |           |            |            |           |
|       |           | 10            |                  |         |             |           |            |            |           |
|       | 6         | 10            |                  | 4       | 20          |           |            |            |           |
|       |           | 20            |                  |         |             |           |            |            |           |
|       |           | 10            |                  |         |             |           |            |            |           |
|       | 8         | 10            |                  | 6.0     | 30          |           |            |            |           |
|       |           | 20            |                  |         |             |           |            |            |           |
|       |           | 10            |                  |         |             |           |            |            |           |
|       | 10        | 10            |                  | 7.5     | 40          | 3.6       | 1.2        | 0.040      |           |
|       |           | 20            |                  |         |             |           |            |            |           |
|       |           | 10            |                  |         |             |           |            |            |           |
| 12    | 10        | 9.0           | 55               | 3.6     | 1.2         | 0.053     |            |            |           |
|       | 20        |               |                  |         |             |           |            |            |           |



■ 软质尼龙气管

| 型号     |           | ③ 尺寸固定型长度 (m) | ④ 气管颜色           | 内径 (mm) | 最小曲率半径 (mm) | 外径精度 (mm) | 重量 (kg/m) |   |    |       |    |    |       |
|--------|-----------|---------------|------------------|---------|-------------|-----------|-----------|---|----|-------|----|----|-------|
| ① 代码   | ② 外径 (mm) |               |                  |         |             |           |           |   |    |       |    |    |       |
| FEPUNS | 4         | 20            | W (白色)<br>B (黑色) | 2.5     | 14          | ±0.1      | 0.009     |   |    |       |    |    |       |
|        |           |               |                  |         |             |           |           | 6 | 21 | 0.017 |    |    |       |
|        |           |               |                  |         |             |           |           |   |    |       | 8  | 34 | 0.023 |
|        |           |               |                  |         |             |           |           |   |    |       |    |    |       |
|        |           |               |                  |         |             |           |           |   |    |       | 12 | 51 | 0.052 |



■ 氟树脂气管

| 型号     |           | ③ 尺寸固定型长度 (m) | 内径 (mm) | 最小曲率半径 (mm) | 外径精度 (mm)     | 最高使用压力 (MPa) | 破坏压力 (MPa) | 重量 (kg/m) |
|--------|-----------|---------------|---------|-------------|---------------|--------------|------------|-----------|
| ① 代码   | ② 外径 (mm) |               |         |             |               |              |            |           |
| FEPUTF | 4         | 10            | 2       | 30          | ±0.1          | 2.5          | 10         | 0.020     |
|        |           | 20            |         |             |               |              |            |           |
|        |           | 10            |         |             |               |              |            |           |
|        | 6         | 10            | 4       | 50          |               |              |            |           |
|        |           | 20            |         |             |               |              |            |           |
|        |           | 10            |         |             |               |              |            |           |
|        | 8         | 10            | 6       | 80          | 1             | 4            | 0.047      |           |
|        |           | 20            |         |             |               |              |            |           |
|        | 10        | 10            | 8       | 120         | +0.1<br>-0.15 | 0.75         | 3          | 0.061     |
|        |           | 20            |         |             |               |              |            |           |
| 12     | 10        | 10            | 200     | 0.75        |               | 3            | 0.074      |           |
|        | 20        |               |         |             |               |              |            |           |