



1 代码 2 D — 3 公称型号
FFCPTK 6 — 2

■ 请按步骤 1~3 选择型号和参数后进行订购。




型号区分: 4 天发货

■ 直立压合接头



FFCPTK
FFCPTY



材质 SUS316

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L	l	对边间距		
1 代码	2 适用气管外径 (mm)						B1	B2	
FFCPTK	4	1	1/8	2	24	9	10	10	
		2	1/4	2	26	11	14	14	
	6	1	1/8	4	26	9	12	12	
		2	1/4	4	28.5	11	14	14	
	8	3	3/8	6	30	12	17	17	17
			1	1/8	6	28	9	14	14
4		3/8	6	30	11	14	14	14	
		1	1/4	6	31	12	17	17	
10	2	1/4	8	32	11	17	17	17	
		3/8	8	33	12	17	17	17	
	4	1/2	8	36	15	22	22	22	
		1	1/4	8	34	11	17	17	
12	3	3/8	10	35	12	17	19	19	
		4	1/2	10	38	15	22	22	


型号		3 公称型号	T R/PT	适用气管内径 (mm)	L	l	对边间距		
1 代码	2 适用气管外径 (mm)						B1	B2	
FFCPTY	4	1	1/8	2.5	24	9	10	10	
		2	1/4	2.5	26	11	14	14	
	8	1	1/8	5	28	9	14	14	
		2	1/4	5	30	11	14	14	
	10	3	3/8	6.5	31	12	17	17	17
			2	1/4	6.5	32	11	17	17
4		3/8	6.5	33	12	17	17	17	
		1/2	6.5	36	15	22	22	22	
12	2	1/4	8	34	11	17	19	19	
		3/8	8	35	12	17	19	19	
	4	1/2	8	38	15	22	22		

① FFCPTK与FFCPTY的区别在于适用气管的内径。请根据使用的气管进行选择。

■ 弯压合接头



FFCLPTK
FFCUNE



材质 SUS316

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L1	L2	l	对边间距		
1 代码	2 适用气管外径 (mm)							B1	B2	
FFCLPTK	4	1	1/8	2	18	20	9	12	10	
		2	1/4	2	21	21	11	14	14	
	6	1	1/8	4	18	21.5	9	12	12	
		2	1/4	4	21	22.5	11	14	14	
	8	3	3/8	6	23	23.5	12	17	17	17
			1	1/8	6	19	24	9	14	14
2		1/4	6	21	24	11	14	14	14	
		3/8	6	23	25	12	17	17		
10	2	1/4	8	22	26.5	11	17	17	17	
		3/8	8	23	26.5	12	17	17	17	
	4	1/2	8	29	28.5	15	22	22	22	
		1	1/4	8	23	27.5	11	17	17	
12	3	3/8	10	27	30	12	22	19	19	
		4	1/2	10	30	30	15	22	22	

型号		3 公称型号	T R/PT	适用气管内径 (mm)	L1	L2	l	对边间距		
1 代码	2 适用气管外径 (mm)							B1	B2	
FFCUNE	4	1	1/8	2.5	18	20	9	12	10	
		2	1/4	2.5	21	21	11	14	14	
	8	1	1/8	5	19	24	9	14	14	
		2	1/4	5	21	24	11	14	14	
	10	3	3/8	6.5	23	25	12	17	17	17
			2	1/4	6.5	22	26.5	11	17	17
4		1/2	6.5	23	26.5	12	17	17	17	
		1/4	6.5	29	28.5	15	22	22	22	
12	2	1/4	8	23	27.5	11	17	19	19	
		3/8	8	27	30	12	22	22	22	
	4	1/2	8	30	30	15	22	22		

橡胶管·快速接头
吸盘及配件